


Product Features



Positive tolerance
Guaranteed tolerance +3%
Reliable power output



High module efficiency
Module efficiency up to 15.7%
Cells efficiency up to 18.5%



Strong compressive strength
Certified to withstand high wind of 2400Pa
and snow loads of 5400Pa




High manufacture standards
certified to high standards by the
most reputable labs According to
IEC:61215: IEC:61730-1/2



International Management System
Manufactured and certified according
to ISO9001, Quality management system

Leading Warranty in PV Industry

- 25 year transferrable power output warranty: 10 years / 90%, 25 years / 80%*
- Linear performance warranty from SIMAX Power
- 12 year material and workmanship warranty




* Please refer to Simax Solar Product Warranty for details.



Electrical Characteristics

Parameters	SM572-190	SM572-195	SM572-200
Peak power [Wp] P_{mpp}	190W	195W	200W
Power Tolerance	0~+3%	0~+3%	0~+3%
Module Efficiency (%)	15.1%	15.3%	15.5%
Open circuit voltage [V] V_{oc}	44.5	44.5	45.1
Maximum Power Voltage [V] (V_{mpp})	36.5	36.5	37.0
Maximum Power Current [A] (I_{mpp})	5.21	5.34	5.41
Short circuit Current [A] (I_{sc})	5.52	5.77	5.88

STC: Irradiance : 1000 W/m²; Spectrum AM 1,5; Cell temperature: 25°C; Wind 0 m/s



Mechanical Characteristics

Solar Cell	Monocrystalline silicon 125 x 125 (mm)
No. of Cells	72 (6 x 12)
Dimensions	1580 x 808 x 35 mm (Option 45 / 50 mm)
Weight	13.5 kg
Front Glass	3.2mm (0.13 inches) tempered glass
Frame	Anodized aluminum alloy



Output

Cable Type	$\varnothing = 4 \text{ mm}^2$
Lengths	L = 900 mm
Junction Box	PV - JB001 MC4

Temperature Coefficients

Nominal Operating Cell Temperature (NOCT)	$45 \pm 2^\circ\text{C}$
Temperature Coefficient of (P_{max})	$-0.39\% / ^\circ\text{C}$
Temperature Coefficient of (V_{oc})	$-0.34\% / ^\circ\text{C}$
Temperature Coefficient of (I_{sc})	$0.052\% / ^\circ\text{C}$

- Provide the best solutions for photovoltaic power generation and technical support
- Provide Cost-effective products
- Provide 12 Years Quality Warranty
- Power out $\geq 90\%$ in 10 years
- Power out $\geq 80\%$ in 25 years



Simax Green New Energy (Europe) GmbH
 Mergenthaler Allee 23 / 25
 65760 Eschborn / Germany
 Tel.: +49 6196 9739 525
 Fax: +49 6196 5929 684
 info@simaxsolar.de
 www.simaxsolar.de



Simax (Australia) Green New Energy Pty Ltd
 5 / 78 Frankston Gardens Drive,
 Carrum Downs, VIC 3210
 Tel: +61 03 9708 2400
 Fax: +61 03 9708 2482
 info@simaxsolar.com
 www.simaxsolar.com.au



Simax (Suzhou) Green New Energy Co.,Ltd
 No. 567 Suzhou Road, Taicang city,
 Jiangsu province, China P.C.: 215400
 Tel: +86 512 5337 8555
 Fax: +86 512 5337 8556
 info@simaxsolar.com
 www.simaxsolar.com

